



HAL
open science

ENSM-SE at CLEF 2006 : Fuzzy Proximity Method with an Adhoc Influence Function

Annabelle Mercier, Michel Beigbeder

► **To cite this version:**

Annabelle Mercier, Michel Beigbeder. ENSM-SE at CLEF 2006 : Fuzzy Proximity Method with an Adhoc Influence Function. Peters, Carol : Clough, Paul : Gey, Fredric : Karlgren, Jussi : Magnini, Bernardo : Oard, Douglas : de Rijke, Maarten : Stempfhuber, Maximilian. Evaluation of Multilingual and Multi-modal Information Retrieval, Springer Berlin / Heidelberg, p 83 - 90, 2007, 10.1007/978-3-540-74999-8_11 . emse-00680435

HAL Id: emse-00680435

<https://hal-emse.ccsd.cnrs.fr/emse-00680435>

Submitted on 1 May 2024

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

ENSM-SE at CLEF 2006 : Fuzzy Proximity Method with an Adhoc Influence Function

Annabelle Mercier and Michel Beigbeder

École Nationale Supérieure des Mines de Saint-Étienne,
158 cours Fauriel, 42023 Saint-Etienne Cedex 2, France
{annabelle.mercier,mbeig}@emse.fr

Abstract. We experiment a new influence function in our information retrieval method that uses the degree of fuzzy proximity of key terms in a document to compute the relevance of the document to the query. The model is based on the idea that the closer the query terms in a document are to each other the more relevant the document. Our model handles Boolean queries but, contrary to the traditional extensions of the basic Boolean information retrieval model, does not use a proximity operator explicitly. A single parameter makes it possible to control the proximity degree required. To improve our system we use a stemming algorithm before indexing, we take a specific influence function and we merge fuzzy proximity result lists built with different width of influence function. We explain how we construct the queries and report the results of our experiments in the ad-hoc monolingual French task of the CLEF 2006 evaluation campaign.

1 Introduction

In the information retrieval domain, systems are based on three basic models: the Boolean model, the vector model and the probabilistic model. These models have many variations (extended Boolean models, models based on fuzzy sets theory, generalized vector space model, . . .) [1]. However, they are all based on weak representations of documents: either sets of terms or bags of terms. In the first case, what the information retrieval system knows about a document is whether it contains a given term or not. In the second case, the system knows the number of occurrences – the *term frequency*, *tf* – of a given term in each document. So whatever the order of the terms in the documents, they share the same index representation if they use the same terms. Noteworthy exceptions to this rule are most of the Boolean model implementations which propose a NEAR operator [2]. This operator is a kind of AND but with the constraint that the different terms are within a window of size n , where n is an integral value. The set of retrieved documents can be restricted with this operator. For instance, it is possible to discriminate between documents about “data structures” and those about “data about concrete structures”. Using this operator results in an increase in precision of the system [3]. But the Boolean systems that implement a NEAR operator share the same limitation as any basic Boolean system: these systems are not

able to rank the retrieved documents because with this model a document *is* or *is not* relevant to a query. Different extensions have been proposed to the basic Boolean systems to circumvent this limitation. These extensions represent the documents with some kind of term weights. Most of the time these weights are computed on a *tf* basis. Some combining formulas are then applied to compute the document score given the term weights and the query tree. But these extensions are not compatible with the NEAR operator. Some researchers have thus proposed models that attempt to directly score the documents by taking into account the proximity of the query terms within them.

2 Uses of Proximity

Three methods have been proposed to score documents taking into account different sets of intervals containing the query terms. These methods differ in the set of intervals that are selected in a first step, and then in the formulas used to compute the score for a given interval. The method of Clarke et al. [4] selects the shortest intervals that contain all the query terms (this constraint is relaxed if there are not enough retrieved documents), so the intervals cannot be nested. In the method of Hawking et al. [5], for each query term occurrence, the shortest interval containing all the query terms is selected, thus the selected intervals can nest. Rasolofo et al. [6] chose to select intervals only containing *two* terms of the query, but with the additional constraint that the interval is shorter than five words. Moreover, passage retrieval methods indirectly use the notion of proximity. In fact, in several methods, documents are ranked by selecting documents which have passages with a high density of query terms, that is to say documents where the query terms are near to each other [7,8,9]. The next section presents our method which scores documents on the basis of term proximity.

3 Fuzzy Proximity Matching

To address the problem of scoring the documents taking into account the relative order of the words in the document, we have defined a new method based on a *fuzzy proximity* [10] between each position in the document text and a query. This fuzzy proximity function is summed up over \mathbb{Z} to score the document.

We model the fuzzy proximity to an occurrence of a term with an influence function f that reaches its maximum (value 1) at the value 0 and decreases on each side down to 0. Different types of functions (Hamming, rectangular, gaussian, etc.) can be used. We used an adhoc and a triangular one shown in Figure 1. In the following, the examples and the experiments will be based on a triangular function $x \mapsto \max(\frac{k-|x|}{k}, 0)$. The constant k controls the support of the function and this support represents the extent of influence of each term occurrence. A similar parameter can be found for other shapes.

So, for a query term t , the fuzzy proximity function to the occurrence at position i of the term t is $x \mapsto f(x - i)$. Now, we define the term proximity




Fig. 1. The adhoc and triangular influence functions used in experiments

function w_t^d which models the fuzzy proximity at the position x in the text to the term t by combining the fuzzy proximity functions of the different occurrences of the term t :

$$x \mapsto w_t^d(x) = \max_{i \in Occ(t,d)} f(x - i)$$

where $Occ(t, d)$ is the set of the positions of the term t in the document d and f is the influence function.

The query model is the classical Boolean model: A tree with terms on the leaves and OR or AND operators on the internal nodes. At an internal node, the proximity functions of the sons of this node are combined in the query tree with the usual fuzzy set theory formulas. So the fuzzy proximity is computed by

$$w_q^d \text{OR } q' = \max(w_q^d, w_{q'}^d)$$

for a disjunctive node and by

$$w_q^d \text{AND } q' = \min(w_q^d, w_{q'}^d)$$

for a conjunctive node. With a post-order tree traversal a fuzzy proximity function to the query can be computed at the root of the query tree as the fuzzy proximity functions are defined on the leaves.

So we obtain a function w_q^d from \mathbb{Z} to the interval $[0, 1]$. The result of the summation of this function is used as the score of the document:

$$s(q, d) = \sum_{x=-\infty}^{+\infty} w_q^d(x) .$$

Thus, the computed score $s(q, d)$ depends on the fuzzy proximity functions and enables document ranking according to the query term proximity in the documents.

4 Experiments and Evaluation

We carried out experiments within the context of the CLEF 2006 evaluation campaign in the ad-hoc monolingual French task¹. We used the retrieval search engine LUCY² which is based on the Okapi information retrieval model [11] to

¹ <http://clef.isti.cnr.it/>

² <http://www.seg.rmit.edu.au/lucy/>

index this collection. It was easy to adapt this tool to our method because it keeps the positions of the terms occurring in the documents in the index. Thus, we extended this tool to compute the relevance score values for our fuzzy proximity matching function.

Documents in the CLEF 2006 test collection are newspapers articles in XML format from *SDA* and *Le Monde* of the years 1994 and 1995. For each document (tag <DOC>), we keep the fields <DOCNO> with the tag and the document number, the textual contents of the tags <TX>, <LD>, <TI>, <ST> for *SDA French* and <TEXT>, <LEAD1>, <TITLE> for *Le Monde* 1995. We used the topics and the relevance judgements to evaluate the different methods by the `trec_eval` program.

4.1 Building the Queries

Each topic is composed of three tags: <FR-title>, <FR-desc>, <FR-narr>. Two sets of queries were built for our experiments.

Automatically built queries. For this set, a query is built with the terms from the title field where the stop words³ are removed. Here is an example with the topic #278. The original topic is expressed by:

```
<top>
<num> 278 </num>
<FR-title> Les moyens de transport pour handicapés</FR-title>
<FR-desc> A quels problèmes doivent faire face les personnes
handicapées physiques lorsquelles empruntent les transports
publics et quelles solutions sont proposées ou adoptées?
</FR-desc>
<FR-narr> Les documents pertinents devront décrire les
difficultés auxquelles doivent faire face les personnes
diminuées physiquement lorsquelles utilisent les transports
publics et/ou traiter des progrès accomplis pour résoudre ces
problèmes.
</FR-narr>
</top>
```

First, the topic number and the title field are extracted and concatenated:

```
278 moyens transport handicapés
```

From this form, the queries are automatically built by simple derivations:

```
Lucy:                278 moyens transport handicapés
conjunctive fuzzy proximity: 278 moyens & transport & handicapés
disjunctive fuzzy proximity: 278 moyens | transport | handicapés
```

³ Removed stop words: à, aux, au, chez, et, dans, des, de, du, en, la, les, le, par, sur, uns, unes, une, un, d', l'.




Fig. 2. Okapi Lucy - Result with stemming at indexing (LucyTitle, StemManualLucy, TitleDescManualLucy) and no stemming (LucyTitleNoStem, LucyManualNoStem)




Fig. 3. Fuzzy Proximity with $k = 100$ - Result with stemming at indexing (ConjTitle100, StemManual100, TitleDescManual100) and no stemming (ConjNoStem100, ManualNoStem100).

and they provide the baselines for the comparison with our method. The recall precision results are provided in Figure 2.

We can see that the runs with no stemming step before indexing have less precision than the others. Figure 3 also shows that the stemming step provide better results. But we can see that the run TitleDescManual is above the ConjTitle100 which means that the words added for “stemming” queries increase the precision results. Figure 4 shows the differences between the Okapi Lucy method and the fuzzy proximity method. We can see that our method is better




Fig. 4. Fuzzy Proximity with $k = 100$ - Result with stemming at indexing (ConjTitle200, StemManual200) and no stemming (LucyTitleNoStem, ManualNoStem200)

than the Lucy one (ManualNoStem200 vs. LucyTitleNoStem; StemManual200 vs. ConjTitle200). We can note the run with stemming at indexing and at query time is the best.

5 Conclusion

We have presented our information retrieval model which takes into account the position of the query terms in the documents to compute the relevance scores. We experimented this method on the CLEF 2006 Ad-Hoc French test collection. In these experiments, we submit runs which use different k values in order to retrieve more documents with our method. We plan to study in detail the fusion of result lists and explore the idea to merge results from runs built with different values of parameter k . Another idea is to adapt the value of this parameter with respect to the document size and then introduce a kind of normalisation.

The main results of our CLEF experiments regard the comparison between stemming treatment at the indexing time or stemming simulation at query time : a detailed analysis of this work is available in [10] where we show the comparative benefits of stemming in the two phases. The results of this study lead us to think that a human-assisted method can be developed to build boolean queries. Perhaps, the user should add query words suggested by a thesaurus in order to complete the boolean queries and retrieve more documents with our method. In our next experiments, we plan to adapt the fuzzy proximity method to structured documents and apply this to the CLEF collection by using the title field and the text field of the XML documents differently.

References

1. Baeza-Yates, R., Ribeiro-Neto, B.: *Modern Information Retrieval*. ACM Press / Addison-Wesley, New York (1999)
2. Salton, G., McGill, M.J.: *Introduction to Modern Information Retrieval*. McGraw-Hill Book Company, New York (1983)
3. Keen, E.M.: Some aspects of proximity searching in text retrieval systems. *Journal of Information Science* 18, 89–98 (1992)
4. Clarke, C.L.A., Cormack, G.V., Tudhope, E.A.: Relevance ranking for one to three term queries. *Information Processing and Management* 36(2), 291–311 (2000)
5. Hawking, D., Thistlewaite, P.: Proximity operators - so near and yet so far. In: Harman, D.K. (ed.) *The Fourth Text REtrieval Conference (TREC-4)*, Department of Commerce, National Institute of Standards and Technology, pp. 131–143 (1995)
6. Rasolofo, Y., Savoy, J.: Term proximity scoring for keyword-based retrieval systems. In: Sebastiani, F. (ed.) *ECIR 2003*. LNCS, vol. 2633, pp. 207–218. Springer, Heidelberg (2003)
7. Wilkinson, R.: Effective retrieval of structured documents. In: *SIGIR '94, Proceedings of the 17th annual international ACM SIGIR conference on Research and development in information retrieval*, pp. 311–317. Springer, New York (1994)
8. De Kretser, O., Moffat, A.: Effective document presentation with a locality-based similarity heuristic. In: *SIGIR '99: Proceedings of the 22nd ACM SIGIR Annual International Conference on Research and Development in Information Retrieval*, pp. 113–120. ACM, New York (1999)
9. Kise, K., Junker, M., Dengel, A., Matsumoto, K.: Passage retrieval based on density distributions of terms and its applications to document retrieval and question answering. In: Dengel, A., Junker, M., Weisbecker, A. (eds.) *Reading and Learning*. LNCS, vol. 2956, pp. 306–327. Springer, Heidelberg (2004)
10. Mercier, A.: *Modélisation et prototypage d'un système de recherche d'informations basé sur la proximité des occurrences de termes de la requête dans les documents*. Ph.d dissertation, Ecole Nationale Supérieure des Mines de Saint Etienne, Centre G2I (2006)
11. Robertson, S.E., Walker, S., Jones, S., Hancock-Beaulieu, M.M., Gatford, M.: Okapi at trec-3. In: Harman, D.K. (ed.) *Overview of the Third Text REtrieval Conference (TREC-3)*, Department of Commerce, National Institute of Standards and Technology, pp. 109–126 (1994)
12. Mercier, A.: Étude comparative de trois approches utilisant la proximité entre les termes de la requête pour le calcul des scores des documents. In: *INFORSID 2004*, pp. 95–106 (2004)