

# **An Exact Method for the Assembly Line Re-balancing Problem**

Fatme Makssoud, Olga Battaïa, Alexandre Dolgui

## **To cite this version:**

Fatme Makssoud, Olga Battaïa, Alexandre Dolgui. An Exact Method for the Assembly Line Rebalancing Problem. 20th Advances in Production Management Systems (APMS), Sep 2013, State College, PA, United States. pp.159-166, 10.1007/978-3-642-41266-0\_20. emse-00880913

# **HAL Id: emse-00880913 <https://hal-emse.ccsd.cnrs.fr/emse-00880913v1>**

Submitted on 2 Feb 2017

**HAL** is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.



[Distributed under a Creative Commons Attribution 4.0 International License](http://creativecommons.org/licenses/by/4.0/)

## An exact method for the assembly line re-balancing problem

Fatme Makssoud, Olga Battaïa, and Alexandre Dolgui

LIMOS, École des Mines de Saint-Étienne, France {makssoud,battaia,dolgui}@emse.fr

Abstract. In this paper, we propose a mathematical optimisation model to solve the simple assembly line rebalancing problem. This problem arises when an existing assembly line has to be rebalanced in order to meet new production requirements. In this paper, a Mixed Integer Program is proposed for solving this problem with the objective to minimize the number of changes in the initial line. The computational experiments show the efficacy of the proposed method.

Key words: Balancing and rebalancing of assembly lines; Binary integer programming;

#### 1 Introduction and related literature

The assembly line consists of a number of consecutive workstations. Products are assembled by means of the successive execution of tasks in workstations as shown in Figure 1.



Fig. 1. Assembly line

The most known formulation of the Simple Assembly Line Balancing Problem (SALBP) aims to find a minimal number of workstations required for assigning a given set V of tasks taking into account precedence and cycle time constraints. The precedence constraints are given by a directed acyclic graph  $G = (V, E)$  over this set of tasks, where each edge  $(i, j) \in E$  indicates that task i is an immediate predecessor of task  $j$  and therefore has to be assigned to a prior or the same workstation as task j.

Each task  $j \in V$  is also characterized by its time,  $t_j$ . The sum of task times of the tasks assigned to the same workstation has to not exceed a given cycle time denoted by  $T_0$ . This problem is known to be NP-hard. Even if it was introduced in the literature almost 60 years ago [10], many recent studies still address it [2, 3, 7, 9, 11].

However, because of frequent changes in the product characteristics and demand, the problem that arises more frequently than initial line balancing problem is how to reassign the set of the tasks in order to meet new production requirements while minimize the number of modifications to be done in the initial line. We call this problem Simple Assembly Line Rebalancing Problem (SALReBP) and propose an exact method to solve it. Indeed, until now rebalancing problems for production lines have been principally addressed by means of approximate methods. Heuristics and genetic algorithms were used for solving stochastic assembly line rebalancing problem by Gamberini et al. [5, 4]. For the case of a vehicle assembly line, three heuristic methods have been developed by Grangeon et al. [6]. A COMSOAL based heuristic for re-balancing of assembly lines that determines a fixed task sequence for a number of different cycle times was proposed by Agpak [1].

The remainder of this paper is organized as follows. A formal definition of the SALReBP is presented in the next section. The linearization of the model proposed is described in Section 3. An illustrative example is given in Section 4. A computational study is presented in Section 5 and concluding remarks are given in Section 6.

#### 2 Formal problem definition and mathematical model

In this section, we present a formal definition of the SALReBP. As mentioned before, we denote by  $T_0$  the cycle time and by  $m$  the number of workstations. Let  $V$  be the set of tasks to be allocated.

The following notations are used in our mathematical model:

– Indices:

 $i, j$  for tasks,

- $k$  for workstations.
- Parameters:

V the new set of tasks,  $j \in V$ ,

 $t_i$  the processing time of task j,  $j \in V$ ,

 $M = \{1, 2, ..., m\}$  is the set of workstations in the existing line,

 $L = \{1, 2, ..., l\}$  is the set of workstations in the new line, where l is an upper bound on the number of workstations for new line.

 $Q(j)$  is the interval of workstations in the upgraded line, where task  $j \in V$ 

can be assigned. It is calculated using the precedence constraints.

– Decision variables:

 $x_{jk}^* = 1$  if task  $j \in V^* \subset V$  is assigned to workstation k in the initial configuration, 0 otherwise. Set  $V^*$  contains tasks j such that for  $x_{jk}^* = 1, k \in Q(j)$ ;  $x_{jk}^* = 0$  for all  $k > m$ , constraint 7 in model (1) - (7);

 $y_{jk} = 1$  if task  $j \in \bigcap V$  is assigned to workstation k in the new solution, 0 otherwise;  $y_{jk} = 0$  for all  $k \notin Q(j)$ , constraint 6 in model (1) - (7).

The following model is used for the presented assembly line rebalancing problem. The objective function (1) consists in minimizing changes in the existing task assignment. Constraint  $(2)$  guarantees that every task j is assigned to one and only one workstation. Constraint (3) imposes the precedence constraints. Constraint (4) ensures that the total duration of the tasks assigned to workstation  $j$  does not exceed cycle time. Constraint  $(5)$  deals with the impossibility of executing certain tasks at the same workstation. Constraint (6) ensures that the variables outside intervals  $Q(i)$  are set to 0.

$$
Minimize \sum_{j \in V^*} \sum_{k \in L} |x_{jk}^* - y_{jk}| \tag{1}
$$

$$
\sum_{k \in Q(j)} y_{jk} = 1, \forall j \in V \tag{2}
$$

$$
\sum_{k \in L} k y_{ik} \le \sum_{k \in L} k y_{jk}, \forall (i, j) \in A
$$
 (3)

$$
\sum_{j \in V} t_j y_{jk} \le T_0, \forall k \in L \tag{4}
$$

$$
y_{ik} + y_{jk} \le 1, \forall \{i, j\} \in E, \forall k \in L
$$
\n
$$
(5)
$$

$$
y_{jk} = 0, \forall j \in V, \forall k \notin Q(j)
$$
 (6)

$$
x_{jk}^{*} = 0, \forall j \in V, \forall k > m \tag{7}
$$

#### 3 Linearization of the model

In the following, we propose a method to linearize the proposed model.

**Lemma 1** Let  $x, y, z \in \{0, 1\}$ . Then the following logical expression

if 
$$
x = 1
$$
 and  $y = 1$ , then  $z = 1$ 

can be modeled as follows:

$$
x + y \leq z + 1.
$$

**Lemma 2** Let  $x, y \in \{0, 1\}$ . Then the following non-linear expression

$$
z:=\mid x-y\mid
$$

can be linearized using the following inequalities

$$
x + y \le (1 - z) + 1,
$$
  
\n
$$
x + (1 - y) \le z + 1,
$$
  
\n
$$
(1 - x) + y \le z + 1,
$$
  
\n
$$
(1 - x) + (1 - y) \le (1 - z) + 1,
$$

It is evident to see that  $z \in \{0,1\}$ . Moreover, only four following cases are possible: if  $x = 1$  and  $y = 1$ ; then  $z = 0$ 

if 
$$
x = 1
$$
 and  $y = 1$ ; then  $z = 0$ ,  
if  $x = 1$  and  $y = 0$ ; then  $z = 1$ ,  
if  $x = 0$  and  $y = 1$ ; then  $z = 1$ ,  
if  $x = 0$  and  $y = 0$ ; then  $z = 0$ .

Applying for these four cases Lemma 1, we obtain the necessary inequalities. To linearize the problem (1) - (5), we introduce a new variable  $z_{jk} := |x_{jk}^* - y_{jk}|$ . Using Lemma 2, we obtain:

$$
Minimize \sum_{j \in V^*} \sum_{k \in L} z_{jk} \tag{8}
$$

$$
\sum_{k \in Q(j)} y_{jk} = 1, \forall j \in V \tag{9}
$$

$$
\sum_{k \in L} k y_{ik} \le \sum_{k \in L} k y_{jk}, \forall (i, j) \in A \tag{10}
$$

$$
\sum_{j \in V} t_j y_{jk} \le T_0, \forall k \in L \tag{11}
$$

$$
y_{ik} + y_{jk} \le 1, \forall \{i, j\} \in E, \forall k \in L \tag{12}
$$

$$
y_{jk} = 0, \forall j \in V, \forall k \notin Q(j)
$$
\n
$$
(13)
$$

$$
x_{jk}^* = 0, \forall j \in V, \forall k > m \tag{14}
$$

$$
x_{jk}^* + y_{jk} \le (1 - z_{jk}) + 1, \forall j \in V, \forall k \in L
$$
\n
$$
(15)
$$

$$
x_{jk}^* + (1 - y_{jk}) \le z_{jk} + 1, \forall j \in V, \forall k \in L
$$
\n
$$
(16)
$$

$$
(1 - x_{jk}^*) + y_{jk} \le z_{jk} + 1, \forall j \in V, \forall k \in L
$$
 (17)

$$
(1 - x_{jk}^*) + (1 - y_{jk}) \le (1 - z_{jk}) + 1, \forall j \in V, \forall k \in L
$$
 (18)

#### 4 Illustrative example

Let us consider the following case study. The initial assembly line is given in Figure 2. This line has to be rebalanced for a modified product where the following tasks {14, 19, 23, 28, 29} have been deleted and new tasks {31, 32, 33, 34, 35} have been introduced. The task times of all tasks are reported in Table 1. The precedence constraints to be respected are given in Figure 3. Exclusion constraints are :

 $\{\{1, 4\}, \{1, 17\}, \{1, 20\}, \{2, 11\}, \{3, 24\}, \{3, 7\}, \{4, 15\}, \{5, 22\}, \{6, 24\}, \{8, 24\}$ 21}, {9, 22}, {10, 15}, {11, 31}, {12, 13}, {12, 20}, {13, 28}, {15, 17}, {16, 17},  $\{22, 26\}, \{30, 33\}, \{31, 32\}\}\$  and the cycle time  $T_0 = 100$ .

WS <sub>1</sub>	WS <sub>2</sub>	WS <sub>3</sub>	WS <sub>4</sub>	
1 2 3 4 5 6789 11 15 19 26	10 12 13 14 16	17 18 20 21 22	23 24 25 26 28 29 30	

Fig. 2. Initial line

Table 1. Set of tasks V and their times

					Task Time (s)					
	0.93		0.68	13	0.64	21	0.78	30	0.91	
$\overline{2}$	1.06	8	0.16	15	0.09	22	0.64	31	0.72	
3	0.68	9	0.68	16	0.17	24	0.09	32	0.15	
4	0.16	10	0.16	17	0.09	25	0.17	33	0.19	
5	0.68			18	0.12	26	0.09	34	0.33	
6	0.16	12	0.78	20		27	0.12	35	0.97	

The optimal solution was obtained in 0.36 second and consists to reassign the following tasks: {2, 4, 10, 12, 21, 31, 32, 33, 34, 35}, they are shown in bold in Figure 4 that illustrates the rebalanced line.

#### 5 Computational results

The proposed method was evaluated on a dataset that consists of 42 instance problems of 25 tasks each. For each initial problem, 3 versions of the modified product were generated: (1) by changing 25% of tasks (five tasks deleted and five added); (2) by changing 50% of tasks (five tasks deleted and eight added); (3) by changing 75% of tasks (five tasks deleted and fourteen added).



Fig. 3. The new precedence diagram.

WS <sub>1</sub>	WS <sub>2</sub>	WS <sub>3</sub>	WS <sub>4</sub>	WS <sub>5</sub>
1 3 5 6 9 11 78 15 27	4 13 16 17 20 21	2 10 12 22 33	24 25 26 30 31	32 34 35

Fig. 4. Rebalanced line

The computational results are respectively presented in Tables 2-4, where the values of the objective function indicating how many tasks were reassigned and the solution time are given. Experiments were carried out on  $PC$  Intel $(R)$ , 2.20 GHz, with 8 Go RAM. The model was coded in C++ with ILOG CPLEX 12.4.

### 6 Conclusion

The problem of assembly line rebalancing was addressed. We have presented a mathematical optimization model that aims at minimizing the number of changes in the initial line. On the basis of an industrial case study, it was shown that the model proposed can be successfully applied in real world environment. The experimentation revealed that the model is capable of solving problems with up to 40 tasks in the precedence diagram.

The further research will undertake a more comprehensive computational experiment in order to evaluate the problem's size limit for which the exact method

Instance tasks			Time(s) Instance tasks			Time(s) Instance tasks		Time(s)
	number Changed			number Changed			number Changed	
$\mathbf{1}$	22	0.45	15	4	0.07	29	17	$1.6\,$
$\overline{2}$	22	0.42	16	14	0.92	30	13	1.62
3	8	0.12	17	6	0.51	31	10	0.98
$\overline{4}$	12	0.04	18	11	0.1	32	21	0.12
$\overline{5}$	13	0.96	19	12	0.2	33	13	0.31
6	10	0.15	20	5	0.74	34	13	0.07
$\overline{7}$	10	0.09	21	23	0.09	35	24	0.99
8	14	1.49	22	21	0.12	36	11	0.32
9	16	0.93	23	19	0.12	37	14	0.10
10	9	0.09	24	$\overline{4}$	0.68	38	12	1.23
11	24	0.07	25	13	0.43	39	17	0.18
12	13	0.12	26	10	0.14	40	10	0.17
13	11	0.6	27	12	0.1	41	12	0.17
14	22	0.04	28	$\overline{4}$	0.06	42	15	0.87

Table 2. Results for rebalancing :25% Objective function

Table 3. Results for rebalancing :50% Objective function

Instance tasks			Time(s) Instance tasks			Time(s) Instance tasks		Time(s)
	number Changed			number Changed			number Changed	
1	23	0.2	15	6	0.45	29	21	0.51
$\overline{2}$	27	0.54	16	14	0.18	30	13	0.18
3	14	1.04	17	5	0.29	31	10	1.07
4	13	0.4	18	15	0.2	32	20	0.24
5	21	0.29	19	12	0.07	33	15	0.14
6	12	0.51	20	5	0.18	34	16	0.12
	11	0.12	21	23	1.31	35	24	0.29
8	14	0.37	22	20	0.14	36	15	0.14
9	18	0.67	23	20	0.23	37	15	0.18
10	12	0.92	24	4	0.21	38	15	0.31
11	24	0.1	25	12	0.1	39	18	0.2
12	14	0.2	26	11	0.09	40	10	0.17
13	14	0.59	27	13	0.17	41	13	0.6
14	22	0.18	28	10	0.98	42	17	0.53

can be applied and to propose efficient heuristic or metaheuristic methods to obtain sub-optimal solutions for such problems.

### References

- 1. Agpak, K.: An approach to find task sequence for re-balancing of assembly lines. Assembly Automation 30(4) (2010) 378-387
- 2. Battaïa, O., Dolgui, A. : A taxonomy of line balancing problems and their solution approaches. International Journal of Production Economics 142 (2013) 259-277

Instance tasks			Time(s) Instance tasks			Time(s) Instance tasks		Time(s)
	number Changed			number Changed			number Changed	
$\mathbf{1}$	23	1.07	15	12	0.29	29	27	0.45
$\overline{2}$	23	0.85	16	20	0.23	30	18	0.14
3	16	0.96	17	5	0.39	31	16	0.23
4	19	1.09	18	20	0.21	32	26	0.18
5	27	1.35	19	18	0.14	33	21	0.93
6	18	0.63	20	11	0.2	34	22	0.26
$\overline{7}$	15	0.18	21	29	0.24	35	29	0.45
8	20	0.45	22	26	0.12	36	21	0.43
9	24	0.59	23	26	0.18	37	21	0.35
10	17	0.15	24	9	1.06	38	21	0.74
11	30	0.1	25	18	0.1	39	23	0.28
12	20	0.32	26	17	0.15	40	16	0.17
13	19	0.99	27	18	0.34	41	19	0.23
14	27	0.12	28	16	1.13	42	22	1.02

Table 4. Results for rebalancing :75% Objective function

- 3. Bautista, J., Pereira,J.: A dynamic programming based heuristic for the assembly line balancing problem. European Journal of Operational Research 194(3) (2009) 787–794
- 4. Gamberini, R., Gebennini, E., Grassi, A., and Regattieri, A. : A multiple singlepass heuristic algorithm solving the stochastic assembly line rebalancing problem. International Journal of Production Research 47(8) (2009) 2141-2164
- 5. Gamberini, R., Grassi, A., and Rimini, B. : A new multi-objective heuristic algorithm for solving the stochastic assembly line re-balancing problem. International Journal of Production Economics  $102(2)(2006)$  226-243
- 6. Grangeon, N., Leclaire, P., and Norre, S. : Heuristics for the re-balancing of a vehicle assembly line. International Journal of Production Research 49(22) (2011) 6609- 6628
- 7. Kilincci, O.: Firing sequences backward algorithm for simple assembly line balancing problem of type 1.Computers &Industrial Engineering 60(4) (2011) 830–839
- 8. Patterson, J. H., and Albracht, J. J.: Technical NoteAssembly-Line Balancing: Zero-One Programming with Fibonacci Search. Operations Research 23(1) (1975) 166- 172
- 9. Pastor, R., Ferrer, L.: An improved mathematical program to solve the simple assembly line balancing problem. International Journal of Production Research 47(11) (2009) 2943–2959
- 10. Salveson, M. E.: The assembly line balancing problem. Journal of Industrial Engineering, 6(3), 18-25 (1955).
- 11. Sewell, E.C., Jacobson, S.H.: A branch, bound, and remember algorithm for the simple assembly line balancing problem. INFORMS Journal on Computing (2011) doi: 10.1287/ijoc.1110.0462.